



7	OUTER MOULD	PVC WHITE 45P	A/R	
6	SHELL 2	USB 3.1CM TO USB 3.0 AF HUB+ FORNT SHELL	1	
		USB 3.1CM TO USB 3.0 AF HUB+ FRONT SHELL	1	
5	SHELL 2	RJ45(1000M) SLIVER ALU SHELL: L60*W27.5*H16.4mm	1	
4	SHELL 1	USB3.1 CM: SLIVER SHELL L20*W12.3mm	1	
3	CONN 2	PCBA:USB3.0 TO RJ45 (1000M) RTL8153	1	
2	CONN 1	TYPE C/M 夾PCB(C TO 3.0 R2 5.1K 10nf)NICKEL	1	
1	CABLE	USB3.1 (#32*1P+D+AL+MY)*2C+#32*1P+#24*2C+AB PVC WHITE OD4.0MM	1	
NO	PART NO	SPEC	QTY	

(DWG NO)	XY-A1211	(UNIT) MM	<b>weltron</b> <sup>®</sup>	TITLE	USB-C to Gigabit
(REV)	A2	(SCALE)			
(PAGE)	1/1		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: LINEAR: X ± 0.0 Z ± 0.5 XXX ± 0.15 XXXX ± 0.05 ANGULAR: ± 0.5°	PART NO	90-USB-CM-RJ45
(DESIGN)					
(CHECKED)					
(APPROVED)					