



NOTES:FINISH (PLATING THICKNESS IN MICRO-INCHES)
 BODY:GOLD PL. 1.5 MICROINCH MINIMUM
 CENTER CONTACT:GOLD PL 3 MICROINCH MINIMUM

| | | | | |
|------|---------------|----------|------|-------------|
| 8 | INSULATOR | TEFLON | 1 | NONE |
| 7 | BODY | BRASS | 1 | GOLD PLATED |
| 6 | CONTACT PIN | BRASS | 1 | GOLD PLATED |
| 5 | RETAINER RING | Be.Cu | 1 | NONE |
| 4 | GASKET | RUBBER | 1 | NONE |
| 3 | INSULATOR | TEFLON | 1 | NONE |
| 2 | BODY | BRASS | 1 | GOLD PLATED |
| 1 | NUT | BRASS | 1 | GOLD PLATED |
| ITEM | DESCRIPTION | MATERIAL | Q'TY | FINISHED |

| | | | | | | |
|-------------|--------|-----|------------------------|----------|----------|-----------|
| | | | TITLE | | | |
| | | | SMA MALE TO UHF FEMALE | | | |
| PART NAME | 44-911 | △ | SCALE | FIT | DESIGNED | |
| DRAWING NO. | | △ | FRACTIONS | ± | DRAWING | Xw |
| FINISHING | | △ | DECIMALS | ±0.15 | CHECKED | |
| MATERIAL | | △ | 2003/07/16 | A1 | APPROVED | |
| | | SYM | DATE | REVISION | UNITS | M/M |
| | | | | | | 1RD ANGLE |