

NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1. 5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:100 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO+85°
2. OPERATION:0° TO70°

MECHANICAL:


1. HOUSINGG MATERIAL:PC UL94V-0
2. INSERT MATERIAL:FAME RETARDANCY ABS UL94V-0
3. PCB MATERIAL:FR-4 T=1. 6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE STAMP PIN T=0. 30mm
5. IDC CONTACT MATERIAL:PHOSPHOR BRONZE T=0. 50mm WITH TIN PLATING
6. RJ45 JACK ;IFE:750 TIMES MIN
7. IDC LIFE:200 TIMES MIN
8. WIRE:AWG 23-26

Weltron®

PART NO: 44-742-8C5-XX

TITLE

SCALE 1:1



MATERIAL

THIRD ANGLE PROJECTION

CAT 5E INLINE COUPLER