



NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5 AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 100 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE: -40°TO+85°
2. OPERATION: 0°TO70°

MECHANICAL:

1. HOUSINGG MATERIAL: PC
2. INSERT MATERIAL: FAME RETARDANCY ABS
3. PCB MATERIAL: FR-4 T=1.6mm
4. CONTACT MATERIAL: PHOSPHOR BRONZE
STAMP PIN T=0.30mm
5. RJ45 JACK ; LIFE: 750 TIMES MIN

weltron®

SYM	Number	Bill No.of Alteration	Signature	Date
Drawn	Ding jian bo	2015.12.28	Tolerance	
Checked	Ge pei jun	2015.12.28		0.00-20.00 ±0.10
Approved	Wang wei jun	2015.12.28		20.00-50.00 ±0.15
				50.00-100.00 ±0.20
				100.00- ±0.25
				Angle ±30°

Angles Projection	Size	Scale	Unit	Part No.
	A4	X:1	mm	44-742-8C6-XX
Sheet	1 OF 1	Version: A/0	Part Name	In-line Coupler Cat.6 RJ45-RJ45