



weltron®

NOTES:

TECHNICAL CHARACTERISTICS:

1. VIBRATION: 100M/S² (10~500HZ)
2. IMPEDANCE: 75 Ω
3. FREQUENCY RANGE: DC~1GHZ
4. WORKING VOLTAGE: 170V MAX
5. WITHSTAND VOLTAGE: 500V RMS

CONTACT RESISTANCE:

1. CENTER CONTACT: ≤ 10 MΩ
2. OUTER CONTACT: ≤ 5 MΩ
3. INSULATION RESISTANCE: ≥ 1000 MΩ
4. VSWR : STRAIGHT: ≤ 1.20, RIGHT ANGLE: ≤ 1.30
5. DURABILITY (MATING): ≥ 500 TIMES MIN;

ENVIRONMENTAL:

1. STORAGE: -40° TO+85°
 2. OPERATION: 0° TO70°
- MATERIAL: ABS; COPPER (CU)**

Part No. **44-771-451S**

SYM	Number	Bill No. of Alteration	Signature	Date
Drawn	Ding jian bo	2016.1.14		
Checked	Ge pei jun	2016.1.14		
Approved	Wang wei jun	2016.1.14		

Tolerance	
0.00-20.00	±0.10
20.00-50.00	±0.15
50.00-100.00	±0.20
100.00- Angle	±0.25 ±30°

Material	ABS			Part Name	Keystone Jack-3.5mm stereo Female to Female
Angles Projection	Size	Scale	Unit		
	A4	X:1	mm	ERP	
Sheet	1 OF 1	Version: A/0			