

WSP-600F-XX



SPECIFICATION

AC RATING		125V/15A//1875W/60HZ
HOUSING		METAL
COLOR		Light Gray
SOCKETS (TOTAL)		6
POWER CABLE LENGTH (EXPOSED)		6 – 20 Ft.
POWER CABLE JACKET MATERIAL		PVC
POWER CABLE CONDUCTOR SPECIFICATION		COPPER
AC PLUG STYLE		NEMA 15P STRAIGHT
OVERLOAD PROTECTION		15A
SWITCH		LIGHTED BREAKER SW
GAS TUBES FOR GROUND CONNECTION		x
POWER SAFETY SHUT DOWN		YES
MOV	L-N	1x14mm 201KD@250J+
	L-G	1x14mm 201KD@250J+
	N-G	1x14mm 201KD@250J+
ENERGY DISSIPATION		750J
MAX. SURGE CURRENT		13500A
MAX. SURGE VOLTAGE		6KV
VOLTAGE PROTECTION RATING		400V(L-N) 500V(L-G,N-G)
RESPONSE TIME <1 NANOSECOND		YES
SURGE INDICATOR (Protected)		YES- 1 x RED
WIRE FAULT (GROUND)		x
EM1 / RF1 NOISE FILTER	X2 Capacitor	Y
	COIL	-
	FREQUENCY	150Khz~30Mhz
	ATTENUATION	up to 20dB
PACKAGING STYLE		color box
STANDARD EXPORT CARTON DESIGN		YES
CERTIFICATIONS		US STANDARD UL/cUL

