

Weltron®

WSP-600PLF-6BK-RA



SPECIFICATION

AC RATING		125V/15A//1875W/60HZ
HOUSING		PLASTIC
COLOR		BLACK
SOCKETS (TOTAL)		6
POWER CABLE LENGTH (EXPOSED)		6 Ft.
POWER CABLE JACKET MATERIAL		PVC
POWER CABLE CONDUCTOR SPECIFICATION		COPPER
AC PLUG STYLE		NEMA 15P RIGHT ANGLE
OVERLOAD PROTECTION		15A
SWITCH		LIGHTED BREAKER SW
GAS TUBES FOR GROUND CONNECTION		x
POWER SAFETY SHUT DOWN		YES
MOV	L-N	1x14mm 201KD@250J+
	L-G	1x14mm 201KD@250J+
	N-G	1x14mm 201KD@250J+
ENERGY DISSIPATION		750J
MAX. SURGE CURRENT		13500A
MAX. SURGE VOLTAGE		6KV
VOLTAGE PROTECTION RATING		500V(L-N, L-G, N-G)
RESPONSE TIME <1 NANOSECOND		YES
SURGE INDICATOR (Protected)		YES- 1 x RED
WIRE FAULT (GROUND)		x
EM1 / RF1 NOISE FILTER	X2 Capacitor	Y
	COIL	-
	FREQUENCY	150Khz~30Mhz
	ATTENUATION	up to 20dB
PACKAGING STYLE		sleeve
STANDARD EXPORT CARTON DESIGN		YES
CERTIFICATIONS	US STANDARD	UL/cUL

6 outlet

750 JOULES

