

# Weltron®

## WSP-600PLF-XXBK



### SPECIFICATION

AC RATING		125V/15A//1875W/60HZ
HOUSING		PLASTIC
COLOR		BLACK
SOCKETS (TOTAL)		6
POWER CABLE LENGTH (EXPOSED)		3 – 6 – 10 – 15 - 20 – 25 Ft.
POWER CABLE JACKET MATERIAL		PVC
POWER CABLE CONDUCTOR SPECIFICATION		COPPER
AC PLUG STYLE		NEMA 15P STRAIGHT
OVERLOAD PROTECTION		15A
SWITCH		LIGHTED BREAKER SW
GAS TUBES FOR GROUND CONNECTION		X
POWER SAFETY SHUT DOWN		YES
MOV	L-N	1x14mm 201KD@250J+
	L-G	1x14mm 201KD@250J+
	N-G	1x14mm 201KD@250J+
ENERGY DISSIPATION		750J
MAX. SURGE CURRENT		13500A
MAX. SURGE VOLTAGE		6KV
VOLTAGE PROTECTION RATING		500V(L-N, L-G, N-G)
RESPONSE TIME <1 NANOSECOND		YES
SURGE INDICATOR (Protected)		YES- 1 x <b>RED</b>
WIRE FAULT (GROUND)		X
EM1 / RF1 NOISE FILTER	X2 Capacitor	Y
	COIL	-
	FREQUENCY	150Khz~30Mhz
	ATTENUATION	up to 20dB
PACKAGING STYLE		sleeve
STANDARD EXPORT CARTON DESIGN		YES
CERTIFICATIONS		US STANDARD UL/cUL



Weltron®