

## WSP-900RM




### SPECIFICATION

AC RATING	125V/15A/1875W/60HZ	
HOUSING	METAL	
COLOR	BLACK	
SOCKETS (TOTAL)	9	
POWER CABLE LENGTH (EXPOSED)	15ft	
POWER CABLE JACKET MATERIAL	PVC	
POWER CABLE CONDUCTOR SPECIFICATION	COPPER	
AC PLUG STYLE	NEMA 15P STRAIGHT	
OVERLOAD PROTECTION	15A	
SWITCH	UNLIGHTED SW	
GAS TUBES FOR GROUND CONNECTION	x	
POWER SAFETY SHUT DOWN	YES	
MOV	L-N	3x20mm 201KD@350J+
	L-G	2x20mm 201KD@350J+
	N-G	2x20mm 201KD@350J+
ENERGY DISSIPATION	2450J	
MAX. SURGE CURRENT	45500A	
MAX. SURGE VOLTAGE	6KV	
VOLTAGE PROTECTION RATING	400V(L-N) 500V(L-G,N-G)	
RESPONSE TIME <1 NANOSECOND	YES	
SURGE INDICATOR (Protected)	YES- 1 x GREEN	
WIRE FAULT (GROUND)	YES- 1 x GREEN	
EM1 / RF1 NOISE FILTER	X2 Capacitor	Y
	COIL	Y
	FREQUENCY	150Khz~30Mhz
	ATTENUATION	up to 65dB
PACKAGING STYLE	white box	
STANDARD EXPORT CARTON DESIGN	YES	
CERTIFICATIONS	US STANDARD	UL/cUL

METAL

15  
ft.



9 outlet

1U  
MOUNTABLE

2450 JOULES

