



4366

| P1 | P2 |
|----|----|
| 1 | C1 |
| 2 | C2 |
| 3 | C3 |
| 5 | 15 |
| 10 | |
| 6 | |
| 7 | C5 |
| 8 | |
| 9 | 14 |
| | 16 |
| 12 | 7 |
| 13 | C4 |
| 14 | 8 |
| 15 | 6 |

⚠ *NOTE: All relevant materials are complied with RoHS directive .

| | | | | |
|-----|-----------------------------------------------------------------------------------------|----------------|------|----------|
| 4 | Jumper Wire UL1061/26#/1C, OD1.0mm, COLOR WHITE, LENGTH 28mm, DRAWING No. EH002601C-013 | H5SE06-0304W01 | 12 | M304 |
| | MOLDED PE COLOR TRANSPARENT | A5BA02-7777 | | M7777 |
| | MOLDED PVC BEIGE | H1BF01-0304B01 | | M304 |
| 3 | SCREW #4-40, 4.5*15mm | A6AB05-0095 | 2 | M95 |
| 2 | DVI29 FEMALE AND HEX-NUT(4.75*5.5mm), GOLD FLASH ON CONTACTS, WHITE INSULATOR | A1KE10-0636 | 1 | M636 |
| 1 | HD15 MALE, GOLD FLASH ON CONTACTS, BULE INSULATOR | A1CA06-0277U09 | 1 | M108 |
| No. | | | Q'TY | Supplier |

| | | | |
|-------------|-----------------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| APPROVED | | PART NO. : 91-906 | Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm |
| CHECKED | HU | | |
| DRAWING | XIAO | | |
| DATE | 24/JUL/19 | | |
| DESCRIPTION | DVI-A/ D FEMALE/HD DB15 MALE VGA | | UNIT:mm |

